

SuperLift ø267 mm 10,8 ltr

Product no:	8106
Shape:	Round
Available lids:	4108 (Membrane)
	4083 (Standard with centering pieces)

VOLUME

Volume under lid:	10.8 l ± 110 ml	Volume brimful:	11.2 l ± 110 ml
--------------------------	-----------------	------------------------	-----------------

DIMENSIONS

External diameter top:	269 mm ± 3 mm	Height:	249.8 mm ± 1 mm
External diameter bottom:	228.5 mm ± 1 mm		

WEIGHT

Weight:	260 g ± 13 g	Weight plastic handle:	11 g ± 1.1 g
----------------	--------------	-------------------------------	--------------

PERFORMANCE

Stackability - dynamic:	Max: 40 kg top load on bottom container at 23°
Stacking tests:	The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

CLOSURE SYSTEM

Lid type options:	Membrane, Standard, Vented
Closure type:	Peel-off
Protective collar:	Yes
Tamper Evidence type:	Tamper Evidence tab

HANDLE

Standard handle:	Flexible plastic on collar
-------------------------	----------------------------

DECORATION

Decoration available:	Dry Offset, IML, Dry Offset w. laquer	Decoration area offset:	750X190 mm
------------------------------	---------------------------------------	--------------------------------	------------

RAW MATERIAL

Raw material options:	PP	Hot filling:	85-95° C
Masterbatch colours:	Colours according to RPC Superfos standard selected pantone colours.		

Hot temperatures:

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at hot temperatures.



Cold temperatures:

Freezing conditions require special resins available on request.

The RPC Superfos packaging must be tested by the customer with the actual product before approval for use at low temperatures.

QUALITY SPECIFICATIONS

Approvals:	All RPC Superfos Products comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.
Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.
Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.



This drawing is confidential, and should not be handed over to any third party without prior written consent.		Superfos	
Drawing Version		Product Drawing	
Mise à jour	Date	"Superlift 10.8L under lid"	
	16/09/2008 JM	"Diameter 266"	
		Log No "8106"	
		www.superfos.com	
Tolérance +/- 2mm			
Validation le :			



Taastrup, 25th July 2018

Certificate of compliance – EU food legislation

RPC Superfos hereby warrants that our products delivered are in accordance with the data sheet for the product provided. All products are suitable for food applications excluding:

6085, 993, 6769, 981, 996

577, 541, 765, 772, 4547, 552, 9255, 177 (gasket versions only)

products in colours: 255, 375, 475, 523, 575, 577, 941

Compliance:

RPC Superfos further warrants that the products comply with the European Union Commission legislation, with all relevant amendments, listed below:

- Regulation EC No. 1935/2004 on materials and articles intended to come into contact with food
- Regulation No. 10/2011/EC: "Plastic materials and articles intended to come into contact with food".
- Regulation 2023/2006 on rules of Good Manufacturing Practice
- Directive 94/62 on packaging and packaging waste

– together the "Applicable EU Legislation"

The compliance is verified by Overall migration testing at an external accredited laboratory under the following conditions:

Simulants	Test conditions
3 % acetic acid	30 minutes at 90 °C followed by 10 days at 40 °C
50% ethanol	30 minutes at 80 °C followed by 10 days at 40 °C
Olive oil	30 minutes at 90 °C followed by 10 days at 40 °C

The overall migration testing is performed according to method EN1186.

For substances with SML (specific migration limits) values, these are verified by specific migration testing. Test conditions dependent on actual substance. Specific migration testing is performed according to EN13130.

If information on dual use substances, OML or SML values or volume/surface ratio in the individual products is required please contact us.

Product suitability:

The products are suitable for all food types and for any long term storage at room temperature or below.

REACH:

RPC Superfos products are produced from polypropylene polymers, masterbatches, IML's, other labels and inks supplied to us by our suppliers.

As downstream users of these articles it is our responsibility that these articles meet the requirements of the so called REACH legislation (Registration, Evaluation, Authorization, and restriction of Chemicals, 1907/2006 EC with all amendments).

Based on confirmations received from our suppliers we hereby confirm that:

RPC SUPERFOS Head Office

RPC Superfos a/s
Sportorno Allé 8
2630 Taastrup, Denmark

CVR. No. 43 23 95 11 (RPC Superfos a/s)

Tel: +45 5911 1110
Fax: +45 5911 1180
Email: superfos@superfos.com
Web: www.rpc-superfos.com



- all substances covered by REACH Regulation and used in materials supplied to RPC Superfos has been pre-registered
- no substances listed in the ECHA candidate list of Substances of Very High Concern (SVHC) for authorization updated on the 27 June 2018 are present above 0,1 % by weight in our products.

Use of colourants in plastic materials in contact with food

We hereby confirm that according to the information provided by our suppliers, all colourants we use in the production process comply with Resolution AP (89) 1.

Nanotechnology:

We hereby confirm that products produced at any factory within the RPC Superfos Group are produced without the use of nanoparticles and with no use of nanotechnology.

Materials of animal origin - BSE/TSE

RPC Superfos hereby informs that, according to information provided by our suppliers, raw materials we are using can be synthesized from animal by-products, i.e. hydrolysis etc. of animal fats and oils into fatty acids. However, the manufacturing process of tallow derivatives includes a multistep chemical treatment involving high temperatures and long residence times. Therefore it fulfills requirements laid down in Regulations 1069/2009/EC, 142/2011/EC, and the "Note for Guidance EMEA/410/01, rev. 3".

Convention on International Trade in Endangered Species of Wild Fauna and Flora

According to the information provided by our suppliers, raw materials we are using to manufacture our products do not contain any substances derived from any endangered species of fauna and flora.

Bisphenol A and S:

Bisphenol A (BPA) is an industrial chemical used in the production of the hard, clear plastic polycarbonate and in epoxy resins used as a protective lining on the inside of metal-based food and beverage cans. Bisphenol S (BPS) is more heat-stable and photo-resistant than BPA and is seen replacing BPA in polycarbonate and epoxy resins.

RPC Superfos is primarily using polypropylene (PP) plastics and a smaller amount of high density polyethylene (HDPE), for all our products.

RPC Superfos hereby warrants that neither BPA nor BPS is intentionally used in our products.

Phthalates:

RPC Superfos has never intentionally used phthalates in the production of plastic packaging.

Some resin suppliers are using some phthalates in the catalyst system during their production and this may result in traces in the product.

RPC Superfos meets the requirements of EU 10/2011 and any subsequent amendments thereto.

Consequently we are working in collaboration with our suppliers to ensure that any possible trace of phthalates in our product do not exceed the limits stated in 10/2011.

Gluten:

RPC Superfos is not using gluten in our production of plastic packaging. We have evaluated the risk of gluten in our products. The conclusion is that the risk is negligible. None of our raw materials contains gluten and we do not allow eating (or drinking) in our production or warehouses.

Mineral Oil

RPC Superfos hereby confirm that mineral oil is not used in our production of plastic packaging.

Based on information received from our suppliers of IML we confirm that the use of mineral oil have been replaced by vegetable oil. RPC Superfos meets the requirements of EU 10/2011 and any subsequent amendments thereto. Consequently we are on a continuous basis, in collaboration with our suppliers control our processes and perform the required analytical tests to verify compliance.

**Nonylphenols**

RPC Superfos has never intentionally used nonylphenols in the production of plastic packaging. We meet the requirements of EU 10/2011 and any subsequent amendments thereto. Consequently RPC Superfos are only using monomers and additives listed in EU 10/2011.

Chlorine:

Generally the printing ink industry uses low levels of chlorinated organic compounds in the production of printing ink in some colors. The chlorine is part of the synthesis route of the pigments and the chlorine ensures the required coloristic and fastness properties of the inks.

RPC Superfos are in continuous dialog with our suppliers of printing ink to reduce the levels of chlorine. Our ink suppliers do not use substances classified as critical, toxic or highly toxic by the EuPIA Exclusion List, nor do they use chlorinated compounds banned from use under the REACH Regulation (EC) No 1907/2006, Title VIII/Annex XVII.

RPC Superfos meets the requirements of EU 10/2011 and any subsequent amendments thereto.

Consequently we are on a continuous basis, in collaboration with our supplier's document that any possible trace of chlorine in our product does not migrate above the limits stated in 10/2011.

Primary aromatic amines:

Migration of primary aromatic amines is primarily an issue for polyamide food contact materials.

RPC Superfos is using polypropylene (PP) plastics and a smaller amount of high density polyethylene (HDPE), for all products. Further EU10/2011 states that plastic materials and articles shall not release primary aromatic amines, excluding those appearing in Table 1 of Annex I, in a detectable quantity into food or food simulant. The detection limit is 0,01 mg of substance per kg of food or food simulant. The detection limit applies to the sum of primary aromatic. Food contact products produced by RPC Superfos meet the requirements of EU10/2011.

Other chemicals:

The chemical materials listed below are not intentionally used in the manufacture or the formulation of our products and are not expected to be present as RPC Superfos is primarily using polypropylene (PP) plastics and a smaller amount of high density polyethylene (HDPE), for all products, both of which are approved for food contact materials. However, our products have not been tested for these chemical materials:

- formaldehyde
- epoxidised soybean oil (ESBO)
- Melamine

Packaging and packaging waste:

RPC Superfos hereby warrants that our products comply with the European Union Committee Directive 94/62/CE with later amendments and that RPC Superfos meets the national requirements set on basis of these. Consequently we are working on:

- reducing our impact on the environment
- reducing the production of waste
- increasing use of re-cycled material where appropriate

Further as part of complying with the Directive the content of heavy metals (sum of lead, cadmium, mercury and hexavalent chromium) in our products is < 100 ppm.

The management of these requirements is integrated into our environmental management system based on the requirement of ISO14001 and the requirements of EN13430 – Requirements for packaging recoverable by material recycling and EN 13428 – Prevention by source reduction.



Printing inks:

The printing inks used by RPC Superfos are all in compliance with:

- Swiss Ordinance of the FDHA on Materials and Articles (817.023.21)
- EuPIA Guideline on Printing Ink applied to the non-food contact surface packaging materials and articles. The products are produced without inks containing the following substances:
 - Benzophenon
 - 4-Hydroxybenzophenon
 - 4-Methylbenzophenon
 - 2,2'-Dimethoxy-2-phenylacetophenon
 - 1-hydroxy-cyclohexyl phenyl ketone
 - 2,4-diethyl thioanthone (DETX)
 - 2-methyl-4'-(methylthio)-2-morpholinopropiophenone
 - Ethyl-4-dimethylaminobenzoate
 - Methyl-2-benzoylbenzoate

However, in accordance with the Applicable EU legislation it is the responsibility of the customer to ensure that the product supplied by RPC Superfos is suitable for the intended use and that the use is in accordance with the relevant acts of law, statutory orders and other rules and regulations, including the said Directives.

RPC Superfos warrants full traceability of the products delivered throughout the manufacturing process.

RPC Superfos factories are as a minimum certified according to ISO9001 and BRC/IOP.

The present certificate is valid for a period of one year starting from the date first above written.

If you have any questions you are welcome to contact us.

Best regards,

RPC Superfos

A handwritten signature in grey ink that reads 'Kamiński'.

Michał Kamiński
Divisional Quality Manager
michal.kaminski@rpc-superfos.com