



Material and Product data sheet

Material-No. Novelis:	3222400
Product Type:	243500
Product Description:	Aluminium container wrinkled wall, with vertical, curled rim
Intended use:	Suitable for contact with foodstuffs (acc. Regulation 2004/1935/EC) - refrigeration-resistant: -40°C - temperature-resistant: 250°C / 60 minutes - suitable for fatty, aqueous and dry fillings - microwave/oven suitably
Composition: (from inside to outside)	1) Lubricant 0,20-0,30 g/m ² 2) Aluminium foil (acc. EN 602) 3) Lubricant 0,20-0,30 g/m ²
Mechanical Values	
Tensile strength:	150 ±10 N/mm ² (acc. DIN EN 546-2)
Elongation:	> 17% (acc. DIN EN 546-2)
Dimensions	
Top outside:	314,5 x 254,0 mm
Top inside:	298,5 x 238,0 mm
Bottom inside:	263,0 x 202,5 mm
Depth:	60,0 mm
Roll edge:	2,5 mm
Weight:	40,15 g ±6% (entspr. DIN EN 546-3)
Packing	
Type of packing:	Cardboard
Quantity per packing unit:	300 (6x50)
Quantity per pallet:	3.600
Storage notice:	8 - 30°C, max. 50%rH

Quality Control: Quality Control effected by Novelis Deutschland GmbH, Ohle Works

Remarks: Our acknowledgement presupposes that the packaging material is appropriately processed.
Please, be advised that the storage of strongly acidic or alkaline products in direct contact with uncoated aluminium foil should be avoided. In aqueous environment these products can dissolve aluminium, the extent of which would depend on temperature and contact time. The suitability of uncoated aluminium foil for specific applications should be ascertained by the relevant manufacturer / packer.

12.05.2016