



## TECHNICAL DATA SHEET SBP-8106-010

### SUPERLIFT BUCKET – LID NOT INCLUDED



Volume under lid	10.8L	(± 110.0ML)
External diameter top	269.0MM	(± 3.0MM)
External diameter bottom	228.5MM	(± 1.0MM)
Height	249.8MM	(± 1.0MM)
Weight	260.0GR	(± 13.0GR)
Weight plastic handle	11.0GR	(± 1.1GR)

#### Stackability – dynamic Stacking tests

Max: 40kg top load on bottom container at 23°  
The stacking tests have been performed to the standard virgin raw material as stated at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.

Closure type	Peel-off
Protective collar	Yes
Raw material	PP
Hot filling	85-95°C



Hot temperatures	The material chose has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The packaging must be tested by the customer with the actual product before approval for use at hot temperatures.
Cold temperatures	Freezing conditions require special resins available on request. The packaging must be tested by the customer with the actual product before approval for use at low temperatures.
Approvals	The buckets comply with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.
Shelf life	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.
Quality information	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect.