



## TECHNICAL DATA SHEET

### SBP-1786-010



Volume under lid	32.2 l (± 159 ml)
Volume brimful	33.3 l (± 166 ml)
External diameter top	374 mm (± 3.7 mm)
External diameter bottom	304 mm (± 3.0 mm)
Height	418.4 mm (± 4.2 mm)
Weight	996 g (± 30 gr)
Stackability – dynamic Stacking tests	Max: 70 kg top load on bottom container at 23° The stacking tests have been performed to the standard virgin raw material as stated below at 23°C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of stacking and transportation.
Special	For lid SBP-1996 lid ‘stackability filled’ is 76 kg.
Closure type	Flex-off, peel-off
Raw material options	PP



#### Hot temperatures

The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. The packaging must be tested by the customer with the actual product before approval for use at hot temperatures.

#### Cold temperatures

Freezing conditions require special resins available on request. The packaging must be tested by the customer with the actual product before approval for use at low temperatures.

#### Approvals

Complies with the European Union Commission Regulation No. 10/2011/EC with amendments, relating to materials and articles intended to come into contact with food, unless otherwise stated. In accordance with EU legislation, it is the responsibility of the customer to ensure that the supplied product is suitable for the intended use.

#### Shelf life

The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

#### Quality information

Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.